

SUPAPORE TP

Pleated Membrane Filter Cartridge



SupaPore TP Microfiltration cartridges have been designed specifically for use in a wide range of aggressive gas and liquid processing applications. Its naturally hydrophobic PTFE membrane makes this cartridge an ideal choice for systems requiring excellent compatibility, reliability and a consistently high quality filtrate.

Product Features

SupaPore TP cartridges feature:

- A naturally hydrophobic PTFE membrane
- 0.2µm rated filter in liquids and 0.02µm in gases
- Polypropylene support
- Minimal fibre migration



- Wide chemical compatibility
- Validation by bacterial and aerosolised bacteriophage challenge
- Junior cartridge available

All cartridges are thermally bonded and adhesive free. Each unit is pre-flushed with ultra-pure water and integrity tested before final assembly.*

- Can be steam sterilised
- Sanitisable
- Meet current US FDA CFR Title 21 requirements
- Fully integrity testable by Water Intrusion, Bubble Point or Diffusion Flow test¹
- All B grade modules are integrity tested during manufacture

Available in a wide range of grades & absolute rated pore sizes:

- 0.1, 0.2, 0.45, 1.0µm and solvent grade
- General Grade
- Biological Grade

Suitable for most sanitisation regimes including steaming, autoclaving, hot water flush and most common sanitising agents.

(Note: Steaming, autoclaving and hot water sanitisation must use the glass filled end-cap option)



Amazon Filters manufactures a comprehensive range of filter housings for SupaPore TP cartridges including the industrial 50 and 60 Series and the 70 Series for hygienic applications. Please consult our Sales Office for further details on the full range.

Features and Benefits

- Fully Integrity Testable - Water Intrusion, Bubble Point and Diffusional Flow values provided for biological grade pore sizes¹
- Validated² removal ratings for consistent and reliable performance
- Naturally hydrophobic PTFE membrane and polypropylene hardware
- Thermal bonding process eliminates adhesives and ensures minimal extractables
- Identification mark on every cartridge
- Full product guide available

¹B grade only

² See product guides for further details stating test method and rated efficiencies

Industries and Applications

Food and Beverage
Pharmaceutical
Fine Chemicals
Electronics

- CO₂ lines, Sterile vent for storage and transfer tanks
- Solvent filtration, polishing
- Polymers, Aggressive acids, Bases, Solvents, Ozonated DI Water
- Photoresists, Acids, Etch Solutions

AMAZON

SupaPore TP Technical Data

Dimensions

	Standard 10"	Junior 5"
Outside Diameter:	71mm	56mm
Typical Surface Area:	0.75m ²	0.25m ²
Length:	See ordering guide	

Sterilisation and Sanitisation*³

Steam or Autoclave: 135°C for >150 hours
³Applies to single open end cartridges only. For all steaming and hot water applications, the Glass Filled end cap option must be used.

Maximum Operating Conditions

Temperature:	80°C	
Recommended Maximum Differential Pressure:	2.5 Bar	
Forward Flow:	5.0 bar @ 20°C	
Reverse Flow:	3.0 bar @ 20°C	

Recommended change-out differential pressure: 2.5 Bar

Product validation guide available on request. All SupaPoreTP cartridges are manufactured under strict control with batch number identification, giving full traceability on all components.



Materials of Construction

Filter Media:	PTFE
Media Support:	Polypropylene (PP)
Cage, Core & End Caps:	Polypropylene (PP)

Integrity Test Specification

B Grade

Micron Rating	Bubble Point In 60/40 IPA/Water	Diffusion Flow (cc/min/10") In 60/40 IPA/Water	Water Intrusion Flow (cc/10 mins/10")
0.10µm	≥ 1500mbar (22 psi)	≤ 11 @ 900mbar	-
0.22µm	≥ 1000mbar (14.5 psi)	≤ 11 @ 700mbar	≤ 13 @ 2500mbar



BÉTA

industrie

WWW.BETA-INDUSTRIE.NL
 TEL: 0031-79-3415518

AMAZON FILTERS LTD.

ALBANY PARK ESTATE, FRIMLEY ROAD
 CAMBERLEY, SURREY, GU16 7PG
 ENGLAND

Tel. +44 (0) 1276 670600
Fax. +44 (0) 1276 670101
Email. sales@amazonfilters.co.uk
Web. www.amazonfilters.com